

TOTALSORB®

TOTALSORB® is a universal granular material that absorbs large quantities of water, oil and organic wastes such as gasoline, diesel fuel and chlorinated hydrocarbons. Also effective on strong acids and alkaline wastes.

Product Attributes:

- ✓ **Significantly more absorbent than clays and other mineral absorbents.**
- ✓ Non-Biodegradable material (40 CFR 264.314 (e)(ii))
- ✓ When Used Properly, Wastes Will Pass Paint Filter Test (EPA 9095).

Absorbency Performance:

Water	3 -4 X	(± 2.5 lbs to absorb 1 gallon)
USP Mineral Oil	2.5 – 3.5 X	(± 2.5 lbs to absorb 1 gallon)
10W30 Motor Oil	2.5 – 3.5 X	(± 2.5 lbs to absorb 1 gallon)

* Absorbency Factor is the amount of absorbent required to absorb one pound of liquid.

Crash Fluid Absorbency Comparison:

	<u>TOTALSORB®</u>	<u>Oil-Dri®</u>	<u>Solid-A-Sorb®</u>
Used Motor Oil	200–220%	60-65%	130-140%
Antifreeze	215-225%	90-100%	165-175%
Gasoline	155-165%	60-65%	110-115%

* Percent Absorbency is the weight of waste absorbed by one pound of sorbent.
(i.e. 200% Absorbency means 1 lbs of sorbent absorbs 2 lbs of waste)

Packaging:

Available in bulk supersacks and 4 cu. foot bags (27-30 lbs each)

For Samples & Information Contact:



M² Polymer Technologies, Inc.

West Dundee, IL 60118 USA

Phone: 847-836-1393

Fax: 847-836-6483

www.m2polymer.com